

MINIX®

P3 Pro

3 Port

P3 Pro LED GaN Wall Charger

100w Turbo

Ultra-Efficient, Multi-Device Charging Solution
Compact Design, Maximum Performance.

Worldwide Compatibility
100-240V Voltage

 QC 3.0

 PD 3.0



Dynamic Power
Sharing Technology



Multi-Protection
Safety System



US



EU



UK



Universal
Compatibility




Phone



Tablet



Laptop



Console

P3 Pro combines two USB-C ports and one USB-A port to create a next-gen charger that delivers unprecedented power and portability.

Core Advantages

100W High-Power Output

Rapidly charges laptops, tablets, and smartphones simultaneously.

Advanced GaN Technology

Enhances efficiency and reduces heat generation in a compact form.

Real-Time Monitoring

Continuously tracks charging power and status, providing full visibility for enhanced safety.

Simultaneous 3-Device Charging

Equipped with 2x Type-C and 1x Type-A ports for versatile charging.

Universal Protocol Compatibility

Supports PD2.0, PD3.0, QC2.0, QC3.0, AFC, FCP, SCP, Apple 2.4A, DCP 1.5A, ensuring seamless compatibility with a wide range of devices.

Ultra-Compact & Portable Design

Measures just 65x65x31mm and weighs 200g, ideal for travel and daily use.

Enhanced Safety & Performance Features

Intelligent Temperature Control

Measures temperature 2000 times per second, ensuring it stays below international standards to prevent overheating.

Source-Level Temperature Control

Built-in GaN chip minimizes heat generation, maintaining optimal performance and protecting connected devices.

Smart Protection

Includes safeguards against overheating, short circuits, and voltage surges.

Technical Specifications

Category	Details
Model	P3 Pro
Input	100-240V~, 50/60Hz, 2.5A
Single Port Output	USB-C1/C2: 5V=3.0A, 9V=3.0A, 12V=3.0A, 15V=3A, 20V=5A (Max 100W) PPS: 5~11V=5A (Max 45W) USB-A1: 5V=3.0A, 9V=3.0A, 12V=2.5A, 15V=2A, 20V=1.5A (Max 30W)
Combined Output	USB-C1+USB-C2: 65W+30W USB-C1+USB-A1: 65W+30W USB-C2+USB-A1: 7.5W+7.5W USB-C1+USB-C2+USB-A1: 65W+(7.5W+7.5W)
Total DC Output	100W
Material	Plastic
Machine Dimension	65x65x31 mm
Machine Weight	200g
Certifications	PSE, FCC, ETL, WEEE, CE
Operating Conditions	Temperature: 0°C to 25°C Humidity: 10%~90% RH (non-condensing)
Storage Conditions	Temperature: -10°C to 80°C Humidity: 5%~95% RH (non-condensing)