

TP100C

MINIX®

100W GaN III Tech Universal Travel Adapter with USB-C Cable



Worldwide Compatibility



All-in-One Design



Safe & Reliable



"Press and Slide" Buttons



GaN Tech



2 x Fuse



Flame Retardant Material



Child-Proof Outlets



UK



US/JP/CN



EU



AU



100W GaN III Technology



EU Plug: Type c

Austria, Belgium, Denmark, France, Finland, Greece, Hungary, Iceland, Latvia, Norway, Poland, Portugal, Romania, Spain, Sweden, Turkey, etc.

US Plug: Type A

United States of America, Brazil, Cambodia, China, Columbia, Cuba, Haiti, Japan, Laos, Mexico, Panama, Philippines, Thailand, etc.

UK Plug: Type G

Belize, Brunei, Cyprus, Dominica, England, Ghana, Hong Kong, Iraq, Ireland, Macau, Malaysia, Oman, Saudi Arabia, Scotland, Singapore, Uganda, etc.

AUS Plug: Type I

American Samoa, Argentina, Australia, Cook Islands, East Timor, Fiji, Kiribati, Nauru, New Zealand, Okinawa, Samoa, Tonga, Uruguay, Vanuatu, etc.

Universal Travel Adapter



63cm Retractable Type-C Cable



Compact & Portable

Product Name	100W GaN III Tech Universal Travel Adapter with USB-C Cable
Rating	100-250V~, 10A Max, 2500W Max
Input	100-250V~, 50/60Hz, 2.5A
Single Port Output Mode	USB-C1/C2: 5.0V $\overline{=}$ 3.0A 15.0W, 9.0V $\overline{=}$ 3.0A 27.0W, 12.0V $\overline{=}$ 3.0A 36.0W, 15.0V $\overline{=}$ 3.0A 45.0W, 20.0V $\overline{=}$ 5.0A 100.0W. USB-A1/C3: 5.0V $\overline{=}$ 3.0A 15.0W, 9.0V $\overline{=}$ 2.0A 18.0W, 12.0V $\overline{=}$ 1.5A, 18.0W.
Combined Output Mode	USB-C1 + C2: 65.0W + 35.0W USB-C1 + C3/A1: 65.0W + 18.0W USB-C2 + C3/A1: 65.0W + 18.0W USB-C1 + C2 + C3/A1: 65.0W + 20.0W + 18.0W USB-C2 + C3 + A1: 65.0W + 15.0W (C3 + A1) USB-C1 + C2 + C3 + A1: 65.0W + 20.0W + 15.0W (C3 + A1)
Total DC Output	100W
Protocol	Support PD3.0, QC4+, FCP, AFC, PPS, BC1-2 and more
Cable Length	63cm
Material	Platic
Machine Dimension	59.0 * 95.2 * 59.0mm
Machine Weight	145g
Operating Temperature	0~25°C
Operating Humidity	25~ 90% RH, non-condensing
Storage Temperature	-20~85°C
Storage Humidity	10~ 90% RH, non-condensing

