

DATA SHEET

ABSINA

GENERAL DATA

Description:

EV Charging Cable Mode 2 3.7kW 6m

Part no.:

301019

Specification

OLED Display

Input/Output voltage AC110V/230V
 Input frequency 50/60Hz
 Max.output power 1-Phase up to 3.7kW(@230V 16A)
 Max.output current 16A for 1-Phase
 Standard IEC 62752:2016/COR1:2019

16A 00:00:00



230V 8888.88kWh

Charging Standby

Certificate CE

Over voltage protection Yes

Under voltage protection Yes

Over load protection Yes

Short circuit protection Yes

Leakage protection Yes

Over-temp protection Yes

Lightning protection Yes

LED indicators Yes

OLED screen Yes

RCD Type B

Current adjustment Yes

Delay charging adjustment Yes

Ethernet/WIFI/4G/Bluetooth No

Protection degree IP67

Operation temperature "-30°C~60°C"

Relative humidity ≤95%RH

Operating elevation limit ≤2000m

Cooling Natural air cooling

Standby power consumption <0.5W

Charging cable 6m (5.5m+0.5m)

Control box HxWxD=200mm*90mm*52mm

Weight ≤2.1kg

Colour&Material Black;Tempered Glass,PC

16A 02:35:00



230V 16.0A 3.7kW

During Charging

16A 00:00:00



16A

230V 0.0A 0.0kW

Setting Current

16A 00:00:00



5h

230V 0.0A 0.0kW

Delay Charging

author / date:

DG / 24.11.2023

adress:

ABSINA GmbH, Carl-Benz-Strasse 9, 74722 Buchen, Germany