MINIX®

TP45

45W GaN III Tech Universal Travel Charger

Global Compatibility, Compact & Safe Multi-Device Fast Charging

4 Ports

UK

US/JP/CN

EU

AU



PD 3.0

2 × USB-C

QC 3.0

2 × USB-A

Core Features

4-Port (2 × USB-C + 2 × USB-A) Configuration
Supports simultaneous multi-device charging

45W Max Single-Port Output
USB-C up to 45W PD fast charge; USB-A up to 22.5W

GaN III Technology
High efficiency, low heat, stable and durable

Universal Compatibility
Supports PD3.0/QC3.0/PPS/FCP/AFC/SSCP and more protocols

Global Travel Ready
100-250V wide voltage, works in 180+ countries

Ultra-Compact Size
54.7 × 79.5 × 33 mm, lightweight and easy to carry

Multiple Safety Protection
10A fuse + over-current/over-voltage/short-circuit protection

Flame-Retardant Material & Anti-Shock Design
Safer insertion and use

Usable in over 180 Countr es & Regions

Worldwide Compatibility

All-in-One Design

GaN III

GaN Tech

"Press and Slide" Buttons

Safe & Reliable

2 x Fuse

Flame Retardant Material

Child-Proof Outlets

MINIX®

TP45

Model	TP45
Product Name	45W GaN III Tech Universal Travel Adapter
Material	Plastic
Input	100-250V~, 50/60Hz, 1.3A
Rating	100-250V~, 10A Max, 2500W Max
Single Port Output	USB-C1/C2: 5V⎓3A / 9V⎓3A / 12V⎓3A / 15V⎓3A / 20V⎓2.25A (Max 45W); PPS 5-11V⎓4.5A (Max 45W) USB-A1/A2: 5V⎓3A / 9V⎓2A / 12V⎓1.5A (Max 18W); SSCP 10V⎓2.25A (Max 22.5W)
Combined Output	5V⎓4.0A (Total)
Max Total Output	45W
Supported Protocols	USB-C: PD3.0, PD2.0, QC2.0, QC3.0, QC3.0+, SSCP, FCP, AFC, Apple, PPS, BC1.2 USB-A: QC3.0, QC2.0, FCP, AFC, Apple, BC1.2
Dimension	54.7 × 79.5 × 33 mm (Machine)
Package Dimension	85 × 120 × 37 mm
Machine Weight	145g
Environment	Operating Temp: 0~25°C Operating Humidity: 25~90% RH (non-condensing) Storage Temp: -20~85°C Storage Humidity: 10~90% RH (non-condensing)
Safety	10A Fuse, Over-Current / Over-Voltage / Short-Circuit Protection
Certifications	CE, FCC, ROHS, WEEE, PSE

GaN III Tech

